

Soda Gun Jetter Installation Guide

1 to 4 gun unit

Installation of Soda Gun Jetter LLC products must meet all applicable electrical codes and regulations established by national, city, county, or other agencies. It is possible that electrical codes and regulations require that a certified electrical contractor or engineer perform the electrical installation. For questions, contact a certified electrician. **All installations must conform to local plumbing codes. Water installation should be done by a licensed plumber.**

Included in this kit: (1) control unit
(1) ac power adapter
(1) push to connect tee (2 for 4 gun systems)
(2) soda gun holsters (4 for 4 gun systems)
(10) cable ties (20 for 4 gun systems)
100 ft ¼ inch od tubing (200 ft for 4 gun systems)

Tools needed: Diagonal cutters
screwdriver
(optional drill/driver)

1. Mount control unit in close proximity of an ac outlet
2. Replace soda gun holsters with level Soda Gun Jetter Holsters. Insure drain hoses are installed and functional. ***Without proper drainage the system will not function as designed.**
3. Connect supplied blue tubing to the fitting on the bottom of the box. You must insure the tubing is firmly pushed into the connector to avoid possible leakage.
4. Run the tubing to the first soda gun holster area, (Preferably alongside the soda lines) if 1 gun is used cut tubing and install to connector on bottom of holster (insure tubing is firmly pushed into connector) and proceed to step 7.
5. If two guns are used install tee and cut a piece of tubing long enough to reach first holster from tee and connect tee to holster. (insure tubing is firmly pushed into connector)
6. Connect tubing to tee and run the tubing alongside the soda lines to the next holster and connect. (insure tubing is firmly pushed into connector)
7. Secure the tubing using the provided cable ties. Cable wall mounts may be used however they are not provided.
8. For 3 to 4 gun systems repeat steps 2 through 7 using the second fitting on the bottom of the box.

9. Plug ac power adapter into bottom of unit and to ac outlet.
10. Have a certified plumber connect 3/8 pex tubing from water supply.
11. Unit comes programmed and time set for EST. See programming guide to change the time to your time zone.



SODA GUN JETTER LLC

Product Warranty

Soda Gun Jetter LLC products are warranted against defective material and workmanship under normal use and service for one year from the date of manufacture. This limited warranty does not apply to any products that have a normal life shorter than one year or failure and damage caused by chemicals, corrosion, physical abuse, or misapplication. Rubber and synthetic rubber parts such as “O”-rings, diaphragms, PVC tubing, and gaskets are considered expendable and are not covered under warranty. This warranty is extended only to the original buyer of Soda Gun Jetter LLC products. If products are altered or repaired without prior approval of Soda Gun Jetter LLC this warranty is void. Defective units or parts should be returned to the factory with transportation prepaid. If inspection shows them to be defective, they will be repaired or replaced without charge, F.O.B. factory. Soda Gun Jetter LLC assumes no liability for damages. Return merchandise authorization number must be granted in advance of returned units for repair or replacement (See “Merchandise Returns” above).